

Honeywell HLP-6050F Face recognition door machine



HLP-6050F-W



HLP-6050F-B

- One-piece aluminum alloy body with diamond cutting edge design
- 7-inch capacitive touch screen is used to provide a good operating experience
- Adopt 5MP high-definition camera, support 127-degree wide-angle, F2.2 aperture, clearly display visitor images
- Waterproof rating IP55, light-sensitive buttons have lasted for a long time
- Explosion-proof grade IK07, high hardness 6H tempered glass panel, strong and durable
- Human body proximity sensor, the screen lights automatically when the user approaches
- Light sensor, wake up the screen-level numeric keys when the illumination is low
- When the server fails, the unit VTO can still call/open the door/swipe the card
- Support building name letter input
- Can store up to 200,000 access control cards (Mifare cards)
- Support NFC card opening
- Support temporary card time management
- Can display community announcements, property management information, advertising messages
- 6 sets of dry contact input, 4 sets of output
- Support 3 languages (English/Traditional Chinese/Simplified Chinese)
- Support face recognition

Specification:

- CAMERA:
 - 5Mega Pixels, 127 angles of view, aperture F2.2
 - Minimum Illumination: 0.0 LUX
- Screen:
 - 7-Inch Wide Screen TFT LCD (1024*600 Resolution)
 - Capacitive Touch screen support multi-touch, 6H glass, IK07 Explosion-Roof.
- Communication:
 - Network interface:10/100 Base-Tx, RJ45.
- Working Environment:
 - Working temperature: -20C-+55C
 - Working Humidity: <90%
 - IP Rating: IP55
- Cover Body:
 - Aluminum Alloy Body.
 - RT: 140mm x 518mm x 50mm.
 - Installation Method: Recessed installation.
- Other:
 - Light Perception: LED night Lighting.
 - Image Compression group:h.264
 - Swipe: Card type MIFARE Type A, Support 200,000 Cards.
 - Relay Output: 4- output support NC/NO Contact.
 - Input: 6 input-dry contact.